

BERKEBILE OIL COMPANY INC -- BERKEBILE 2+2 DOT 3 BRAKE FLUID B14055 -- 9150-00F056189

MSDS Safety Information

FSC: 9150
 MSDS Date: 03/12/1996
 MSDS Num: CHPMC
 LIIN: 00F056189
 Tech Review: 05/18/1998
 Product ID: BERKEBILE 2+2 DOT 3 BRAKE FLUID B14055
 Responsible Party
 Cage: FO088
 Name: BERKEBILE OIL COMPANY INC
 Box: 715
 City: SOMERSET PA 15501-0715 US
 Info Phone Number: 814-443-1656
 Emergency Phone Number: 814-443-1656

Preparer Co. when other than Responsible Party Co.

Cage: FO088
 Assigned Ind: Y
 Name: BERKEBILE OIL COMPANY, INC.
 Box: 715
 City: SOMERSET PA 15501-0175

Contractor Summary

Cage: FO088
 Name: BERKEBILE OIL COMPANY, INC.
 Box: 715
 City: SOMERSET PA 15501-0175 US
 Phone: 814-443-1656
 Cage: 58011
 Name: BERKEBILE OIL INC THE
 Box: 715
 City: SOMERSET PA 15501-0175 US
 Phone: 814-443-1656

Ingredients

Name: OXIDATION INHIBITOR

Name: GLYCOL ETHERS

Name: POLYGLYCOLS

Name: CORROSION INHIBITOR

Health Hazards Data

LD50 LC50 Mixture: ORAL L50(RAT): >2000 MG/KG
 Route Of Entry Inds - Inhalation: YES
 Skin: YES
 Ingestion: YES
 Carcinogenicity Inds - NTP: NO
 IARC: NO
 OSHA: NO
 Effects of Exposure: EYES: MODERATE IRRITATION/CORNEAL INJURY. SKIN:
 PROLONGED/REPEATED EXPOSURE MAY CAUSE IRRITATION, MORE SEVERE IF SKIN IS
 ABRADED. INGESTION: LOW TOXICITY. LARGE AMOUNTS MAY CAUSE INJURY. MAY

CAUSE LET HARGY.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: IRRITATION, NAUSEA

First Aid: EYES: IRRIGATE W/FLOWING WATER IMMEDIATELY & CONTINUOUSLY FOR 15 MINS. SKIN: WASH OFF IN FLOWING WATER/SHOWER. INHALATION: REMOVE TO FRESH AIR. INGESTION: INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES. NOTE TO PHYSICIAN: SUPPORTIVE CARE. TREATMENT BASED ON JUDGEMENT OF THE PHYSICIAN IN RESPONSE TO REACTIONS OF THE PATIENT.

Handling and Disposal

Spill Release Procedures: KEEP OUT OF SEWERS, STORM DRAINS, SURFACE WATERS & SOIL. DON'T ALLOW TO CONTAMINATE GROUND WATER. SOAK UP W/SUITABLE ABSORBENT MATERIAL & SWEEP/SCOOP UP. DON'T DUMP INTO ANY SEWERS, ON THE GROUND/INTO ANY BODY OF WATER.

Waste Disposal Methods: SEND TO A LICENSED RECYCLER, RECLAIMER/INCINERATOR. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions: PROVIDE SUITABLE TRAINING TO THOSE WORKING W/BRAKE FLUID.

Other Precautions: PRACTICE REASONABLE CARE & PERSONAL CLEANLINESS. ORGANIC LIQUIDS ON HOT FIBROUS INSULATION MAY LEAD TO LOWERING OF THE AUTOIGNITION TEMPERATURE POSSIBLE RESULTING IN SPONTANEOUS COMBUSTION.

Fire and Explosion Hazard Information

Flash Point Method: PMCC

Flash Point Text: 272F

Extinguishing Media: WATER FOG, FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: LARGE: USE ALCOHOL RESISTANT FOAMS. WATER MAY BE USED TO FLUSH TO NON-FLAMMABLE MIXTURES. CONTAIN RUNOFF WATER. WEAR POSITIVE-PRESSURE SCBA & PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard: DIRECT WATER STREAM MAY CAUSE VIOLENT FROTHING, BUT FIRE WATER SPRAY MAY HELP CONTROL SITUATION. WHEN USING WATERSPRAY, PRODUCT TEMP MAY BOIL OVER AT BOILING PT

Control Measures

Respiratory Protection: WHEN AIRBORNE EXPOSURE GUIDELINES/COMFORT LEVELS MAY BE EXCEEDED, USE AN APPROVED AIR PURIFYING RESPIRATOR.

Ventilation: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT FOR MOST CONDITIONS.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEMICAL GOGGLES

Other Protective Equipment: CLEAN BODY COVERING CLOTHING

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH W/SOAP & WATER BEFORE EATING/DRINKING/USING TOILET FACILITIES.

Physical/Chemical Properties

B.P. Text: >430F

Vapor Pres: LOW

Spec Gravity: 1.03

Solubility in Water: COMPLETE

Reactivity Data

Stability Indicator: YES

Materials To Avoid: STRONG OXIDIZING MATERIAL

Hazardous Decomposition Products: CO2, CO & WATER. UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Hazardous Polymerization Indicator: NO

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

Other Information

=====

=====

HAZCOM Label

=====

Product ID: BERKEBILE 2+2 DOT 3 BRAKE FLUID B14055

Cage: FO088

Company Name: BERKEBILE OIL COMPANY, INC.

PO Box: 715

City: SOMERSET PA

Zipcode: 15501-0175 US

Health Emergency Phone: 814-443-1656

Date Of Label Review: 10/12/1999

Hazard And Precautions: EYES: MODERATE IRRITATION/CORNEAL INJURY. SKIN:
 PROLONGED/REPEATED EXPOSURE MAY CAUSE IRRITATION, MORE SEVERE IF SKIN IS
 ABRADED. INGESTION: LOW TOXICITY. LARGE AMOUNTS MAY CAUSE INJURY. MAY
 CAUSE LET HARGY.

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of
 Defense. The United States of America in no manner whatsoever expressly
 or implied warrants, states, or intends said information to have any
 application, use or viability by or to any person or persons outside the
 Department of Defense nor any person or persons contracting with any
 instrumentality of the United States of America and disclaims all
 liability for such use. Any person utilizing this instruction who is not
 a military or civilian employee of the United States of America should
 seek competent professional advice to verify and assume responsibility
 for the suitability of this information to their particular situation
 regardless of similarity to a corresponding Department of Defense or
 other government situation.