# Material Safety Data Sheet



## 1. Product and company identification

Product name Castrol GTX High Mileage 10W-30

MSDS # 463541 Historic MSDS #: 16307000

Code 463541-US12 US13 US81 CA01

Product use Engine oils.

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: (973) 633-2200 Telecopier: (973) 633-7475

**EMERGENCY HEALTH** 

INFORMATION:

1 (800) 447-8735

Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT 1 (866) 4 BP - MSDS

**INFORMATION** (866-427-6737 Toll Free - North America)

email: bpcares@bp.com

#### 2. Hazards identification

Physical state Liquid.

Color Brown.

Emergency overview CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

**Eyes** May cause eye irritation.

Skin May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation

and/or dermatitis.

**Inhalation** May cause respiratory tract irritation.

**Ingestion** Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (Section 11)

#### 3. Composition/information on ingredients

Ingredient name CAS # %

Base oil - highly refined Varies 85 - 90 Zinc alkyl dithiophosphate 68649-42-3 1 - 5

Product name Castrol GTX High Mileage 10W-30 Product code 463541-US12 US13 US81 Page: 1/6

Version 3 Date of issue 05/24/2011. Format US Language ENGLISH

#### 4. First aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention if symptoms occur.

**Skin contact** Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if

symptoms occur.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If potentially dangerous quantities of this material have been

swallowed, call a physician immediately. Get medical attention if symptoms occur.

## 5. Fire-fighting measures

Flash point Closed cup: >200°C (>392°F) [Pensky-Martens.]

Fire/explosion hazards In a fire or if heated, a pressure increase will occur and the container may burst.

Unusual fire/explosion Non-explosive in the presence of the following materials or conditions: open flames, sparks and

hazards static discharge, heat and shocks and mechanical impacts.

**Extinguishing media** 

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable Do not use water jet.

Fire-fighting procedures Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

**Hazardous combustion** 

products

Combustion products may include the following:

phosphorus oxides metal oxide/oxides

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

Protective clothing (fire) Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

#### 6. Accidental release measures

**Personal precautions** 

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Version 3

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent

entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an

appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Product name Castrol GTX High Mileage 10W-30

Date of issue 05/24/2011.

Product code

463541-US12 US13 US81 Page: 2/6

Format US

Language ENGLISH

(US)

(ENGLISH)

#### 7. Handling and storage

Handling Put on appropriate personal protective equipment (see Section 8). Workers should wash hands

and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate

respirator when ventilation is inadequate.

Storage Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-

ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate

containment to avoid environmental contamination.

Other information Sulfur compounds in this material may decompose when heated to release hydrogen sulfide gas

which may accumulate to potentially lethal concentrations in enclosed air spaces. Vapor concentrations of hydrogen sulfide above 50 ppm, or prolonged exposure at lower concentrations, may saturate human odor perceptions so that the smell of gas may not be apparent. Exposure to concentrations of hydrogen sulfide vapor above 500 ppm may cause rapid death. Do not rely on

the sense of smell to detect hydrogen sulfide.

## 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name Occupational exposure limits

Base oil - highly refined ACGIH (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mineral oil, mist

OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mineral oil, mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist,

use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before

reusing.

Personal protection

Eyes Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

**Skin and body** Avoid contact with skin and clothing. Wear suitable protective clothing.

**Respiratory**Use adequate ventilation. In accordance with good industrial hygiene and safety work practices,

airborne exposures should be controlled to the lowest extent practicable.

**Hands** The correct choice of protective gloves depends upon the chemicals being handled, the conditions

of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

## 9. Physical and chemical properties

Physical state Liquid.

Color Brown.

Flash point Closed cup: >200°C (>392°F) [Pensky-Martens.]

Specific gravity 0.87

Viscosity Kinematic: 82 mm²/s (82 cSt) at 40°C

Kinematic: 12 mm<sup>2</sup>/s (12 cSt) at 100°C

**Solubility** insoluble in water.

Product name Castrol GTX High Mileage 10W-30 Product code 463541-US12 US13 US81 Page: 3/6

Version 3 Date of issue 05/24/2011. Format US Language ENGLISH

### 10. Stability and reactivity

Stability and reactivity

The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition** 

products

Hydrogen Sulfide (H2S)

Hazardous polymerization Under normal conditions of storage and use, hazardous polymerization will not occur.

#### 11. Toxicological information

Other Toxicity Data USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Other information Contains low concentration of zinc alkyl dithiophosphate (ZDDP). Concentration is not expected to

cause eye or skin irritation.

Potential chronic health effects

**Carcinogenicity** No known significant effects or critical hazards.

### 12. Ecological information

#### **Ecotoxicity**

No testing has been performed by the manufacturer.

## 13. Disposal considerations

**Waste information** 

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

## 15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

Product name Castrol GTX High Mileage 10W-30

Product code 463541-US12 US13 US81

Page: 4/6

Version 3 Date of issue 05/24/2011.

Format US Language ENGLISH

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: No products were found.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol GTX

High Mileage 10W-30: Immediate (acute) health hazard

**SARA 313** 

Product name CAS number Concentration

Form R - Reporting Zinc alkyl dithiophosphate 68649-42-3 0.67 - 1.3333

Form R - Reporting requirements

Supplier notification Zinc alkyl dithiophosphate 68649-42-3 0.67 - 1.3333

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4): CERCLA: Hazardous substances.: Zinc alkyl dithiophosphate: 1 lb. (0.454 kg); Zinc alkyl dithiophosphate; Zinc alkyl dithiophosphate; Benzene: 10 lbs. (4.54 kg); Arsenic: 1 lb. (0.454 kg);

lead: 10 lbs. (4.54 kg); Cadmium (Non-pyrophoric): 10 lbs. (4.54 kg);

State regulations

Massachusetts The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES,

Substances HYDROTREATED LIGHT PARAFFINIC

New Jersey Hazardous Substances

The following components are listed: ZINC compounds

Pennsylvania RTK Hazardous Substances

The following components are listed: ZINC COMPOUNDS

**California Prop. 65 WARNING:** This product contains a chemical known to the State of California to cause cancer.

white mineral oil; Arsenic

WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm. lead; Cadmium (Non-pyrophoric); Benzene

Other regulations

Canada inventory All components are listed or exempted.

**REACH Status** For the REACH status of this product please consult your company contact, as identified in Section

1.

Australia inventory (AICS)

At least one component is not listed.

China inventory (IECSC)

At least one component is not listed.

Japan inventory (ENCS)

At least one component is not listed.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory

(PICCS)

All components are listed or exempted.

#### 16. Other information

Label requirements CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

HMIS® Rating : Health 1 National Fire

Flammability 1 Protection

Physical 0 Hazard Personal X protection Association (U.S.A.)



**History** 

 Date of issue
 05/24/2011.

 Date of previous issue
 08/11/2010.

Prepared by Product Stewardship

Product name Castrol GTX High Mileage 10W-30 Product code 463541-US12 US13 US81 Page: 5/6

Version 3 Date of issue 05/24/2011. Format US Language ENGLISH

#### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol GTX High Mileage 10W-30 Version 3 Date of issue 05/24/2011. **Product code** 

463541-US12 US13 US81 CA01 Page: 6/6

Format US Language ENGLISH