



MATERIAL SAFETY DATA SHEET

Page 1 of 5

HE175 - DRIVEWAY ASPHALT FILLER & SEAL ER

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 02/11/2008 Product Name: HE175 - DRIVEWAY ASPHALT FILLER & SEAL ER Product Code: HE175	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
petroleum asphalt	mixture		10 - 30
attapulgate	12174-11-7		1 - 5
bentonite	1302-78-9		1 - 5
carbon black	1333-86-4		0 - 1
inert ingredients			<Balance>

EMERGENCY OVERVIEW	
CAUTION! Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.	
Appearance/Odor: Black liquid, faint petroleum solvent odor	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).
Skin Hazards May cause skin irritation and contact dermatitis upon prolonged contact.
Ingestion Hazards May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.
Inhalation Hazards Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.



HE175 - DRIVEWAY ASPHALT FILLER & SEALER

3. Hazards Identification - Continued
Chronic/Carcinogenicity Effects This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.
4. First Aid Measures
Eye In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.
Skin Remove contaminated clothing and shoes. Wash affected areas with soap and water.
Ingestion Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.
Inhalation Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.
5. Fire Fighting Measures
Flash Point: >212 °F Flash Point Method: Setaflash Lower Explosive Limit: not available Upper Explosive Limit: not available
Fire And Explosion Hazards Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.
Extinguishing Media Chemical foam, carbon dioxide (CO2), water fog or dry chemical.
Fire Fighting Instructions Firefighters should wear self-contained breathing apparatus and full protective gear.
6. Accidental Release Measures
Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations. Avoid runoff to waterways and sewers.
7. Handling And Storage
Handling And Storage Precautions Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near strong oxidants or strong acids. Use only with adequate ventilation.
8. Exposure Controls/Personal Protection
Engineering Controls Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.
Eye/Face Protection Safety glasses with side shields or goggles recommended.

HE175 - DRIVEWAY ASPHALT FILLER & SEALER

8. Exposure Controls/Personal Protection - Continued

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

petroleum asphalt

ACGIH TLV-TWA 0.5 mg/m³ (inhalable fraction, as benzene-soluble aerosol)

bentonite

ACGIH TLV-TWA 10 mg/m³ (total dust)

ACGIH TLV-TWA 3 mg/m³ (respirable dust)

OSHA PEL-TWA 15 mg/m³ (total dust)

OSHA PEL-TWA 5 mg/m³ (respirable dust)

carbon black

ACGIH TLV-TWA 3.5 mg/m³

OSHA PEL-TWA 3.5 mg/m³

9. Physical And Chemical Properties

Appearance

black liquid

Odor

faint petroleum solvent odor

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 212-220 °F

Specific Gravity: 1.08

Percent Volatiles: <70

Vapor Pressure: 24@77°F

Vapor Density: >1

pH Factor: not applicable

Solubility: dispersible

Evaporation Rate: <1

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatible Materials

Avoid contact with strong oxidizing agents and acids.

Hazardous Decomposition Products

Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO₂).



HE175 - DRIVEWAY ASPHALT FILLER & SEALER

11. Toxicological Information

Chronic/Carcinogenicity

IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans (Group 2B): carbon black

Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Ingredient(s) - Toxicological Data

carbon black

rat LC50: 6750 mg/m³ 4-hr exposure

12. Ecological Information

No specific information available.

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground Not Restricted

IMDG Not Restricted

IATA Not Restricted

15. Regulatory Information

U.S. Regulatory Information

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Ingredient(s) - State Regulations

petroleum asphalt

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

attapulgitite

California - Proposition 65

carbon black

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: D2A - Very Toxic

Ingredient(s) - Canadian Regulatory Information

carbon black


WHMIS - Ingredient Disclosure List

HE175 - DRIVEWAY ASPHALT FILLER & SEALER

WHMIS - Canada (Pictograms)



NFPA



HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 01/16/2007

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).