



Maintenance Solutions

Dustract VOC

Dust Mop Treatment



For Use On:

Vinyl Tile	Linoleum	Cork
Vinyl	Wood	Terrazzo
Asbestos	Concrete	Quarry Tile
Asphalt Tile	Flagstone	

DESCRIPTION

A high quality dust mop treatment which attracts and holds dust to the dust mops. Ideal for maintaining all types of flooring, including wood, vinyl, terrazzo, concrete synthetic sports floors and sealed or painted surfaces. Daily dust mopping with this product will increase the life and beauty of floors by reducing the abrasive effects of tracked in dirt. Ideal for removing black rubber heel marks.

DIRECTIONS

For a new mop or a mop that has been cleaned thoroughly, use 2 ounces of product per linear foot of dust mop. Sprinkle or course spray on mop strands. Hang treated mop in well-ventilated area until next day's use. Dirt and dust can easily be removed from treated mop by vigorously shaking. For daily care, shake out dust and spread wicks apart. Retreat with 1 ounce of product per linear foot. When mop becomes too soiled, launder and re-treat.

PRODUCT SPECIFICATIONS

Active Ingredients:	100%	Water Miscibility:	None
Color:	Clear	Foam:	None
Odor:	Banana	Sediment:	None
Type:	Paraffin oil	Storage/Stability:	2 years
Solvent Systems:	Mineral spirits	Weight per Gallon:	7.09 lbs./gal.
Flash Point:	> 200° F	Coverage:	2500-3000 sq. ft. per gal.
Viscosity:	Water thin	VOC Content:	0.50 lbs. per gal.

Mop Treatments

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Manufacturer's Name: Misco Products Corporation	Product Name: Dustract VOC
Manufacturer's Address: 1048 Stinson Drive Reading, PA 19605	Generic Name: Dust Mop Treatment
Manufacturer's Phone #: (610) 926-4106	Chemical Family: Paraffinic Oil Blend
	Formula: Proprietary

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Petroleum Distillates	64742-88-7	< 7.0	500 ppm	100 ppm	N/A
Mineral Seal Oil	64742-55-8	95 to 99			
n-Amyl Acetate	628-63-7	0 to 5	100 ppm	100 ppm	N/A

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 316 F. Initial	Specific Gravity: .85
Vapor Pressure: <10mm Hg @ 68 F.	Vapor Density (Air=1): >1
% Volatile: < 7.0%	pH: N/A
Solubility in Water: Nil	Evaporation Rate (Water=1): <1
Physical Description: Slightly viscous clear liquid with pleasant odor.	

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): >200° F. (TCC)
Upper Explosion Limit: N/A
Lower Explosion Limit: N/A
Extinguishing Media: Foam, CO ₂ , Dry Chemical
Special Firefighting Procedures: Do Not Use Water.
Unusual Fire and Explosion Hazards: Drums heated by fire can explode.

SECTION 5-REACTIVITY DATA

Stability: Stable	Hazardous Polymerization: None
Hazards Decomposition Products: Carbon monoxide possible if burned.	Incompatibility (Materials to Avoid): Strong oxidizers.

SECTION 6-STORAGE AND HANDLING INFORMATION

Use only with adequate ventilation. Avoid breathing of vapors or mists. Keep out of reach of children. For use by trained personnel only. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Prolonged or repeated contact may cause irritation or dermatitis.
Eyes: Eye irritant. May cause redness, swelling, or blurred vision.
Inhalation: May cause dizziness or drowsiness.
Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis.

First Aid Procedures:

Skin: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: Get to fresh air. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist.
Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas.
Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: Solvent proof rubber or neoprene.
Eye Protection: Chemical splash goggles.
Other Protective Equipment: Eyewash and fire extinguisher should be located nearby when using.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:	Shipping Information:	HMS Hazardous Materials Identification System
Yes - Fire Hazard	FOR CONTAINERS > 1 Gallon : Cleaning Compound	Health
No - Sudden Release of Pressure Hazard		Flammability
No - Reactivity Hazard	FOR 1 GALLON CONTAINERS : Cleaning Compound	Reactivity
Yes - Immediate (acute) Health Hazard		Personal Protection
No - Delayed (chronic) Health Hazard	FOR CONTAINERS < 1 GALLON : Cleaning Compound	

Health	1
Flammability	1
Reactivity	0
Personal Protection	A

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product