

05-21-04 ✓

01218-XXXX

MATERIAL SAFETY DATA SHEET
 OSHA Hazard Communication
 Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 17
 US Department of Labor
 Printed on 7/02/01 at 09:42:0

Material Identity
 Jacquard Dye-na-Flow

Seq. No. 1 Rev. No. 1
 ASTM D4236-89 Yes
 Certification

SECTION I MANUFACTURER'S NAME AND LOCATION

Manufact. Name Rupert, Gibbon & Spider
 Address line 1 P.O. Box 425
 Address line 2 Healdsburg, CA 95448
 Address line 3 USA
 Info. Tel. No. 707-433-9577 Emerg. Tel. No. 1(800)468-6942
 Prep. Date 1/01/03 Responsible Person Michael Katz
 Title President

SECTION II HAZARDOUS INGREDIENT/IDENTITY/STANDARDS/CONTENT INFORMATION

Ingredient Listing	CAS No.	OSHA PEL	ACGIH TLV	STEL
Acrylic Polymer Emulsi	N/L	N/L	N/L	N/L
Defoamer	N/L	N/L	N/L	N/L
Surfactant	N/L	N/L	N/L	N/L
Silicone Emulsion	N/L	N/L	N/L	N/L
Caster Oil	N/L	N/L	N/L	N/L
Titanium Dioxide	13463-67-7	10 mg/m3	10 mg/m3	N/L
Pigments	Mixture	N/L	N/L	N/L

This product has not been tested in animals but the Toxicologist reviewing this product has judged the formulation to be "Not Rated Acutely Toxic". It is not likely to be an irritant to the eyes or skin. However, as with all chemical mixtures, it is prudent to avoid contact with eyes and skin.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/D	Deg. F (Cel)	Spec. Grav. N/D
Melting Point	N/D	Deg. F (Cel)	(H2O=1)
Vapor Pressure	N/D		Vapor Density N/D
Evaporation Rate	N/D		Water Solubility N/D
Odor	Odor of Latex paint.	Appearance	Colored liquid paint in 33 colors.

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point N/D Deg. F. (Cel) Flash Pt. Method N/D
 Lower Flam. Limit N/D % Upper Flam. Limit N/D
 Exting. Medium Use water, foam, carbon dioxide or dry chemical. This product not likely to burn when wet.
 Specialized Fire Fighting Proc. None required for this material. However, when fighting any fire, wear positive pressure self-contained NIOSH approved breathing equipment.
 Unusual Fire & Explosion Hazard Sealed Containers may rupture; Paint films may burn. This product presents no unusual fire or explosion hazards.

SECTION V REACTIVITY DATA

Stable (Unstable)	Conditions Strong oxidizing agents.
Stable (yes/no)	Yes to avoid
Incompat. (Avoid)	Avoid strong oxidizing agents.
Haz. Decomp. (y/n)	Not Likely
Cond. to Avoid.	Haz. Polym. (yes/no) Not Likely.
	None known.

V-1895

Confirm all information prior to use

Abbreviations: Not Applicable N/A.. Not Flammable N/F Ceiling Value C
 Not Determined N/D
 Not Known N/K Not Listed N/L

Permissible Exposure Limit PEL ACGIH Threshold Limit Value TLV

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intended use. No other warranty is given. (Only Reg. for ACGIH)

Item Numbers: 01218-1008, 01218-1010, 01218-1013, 01218-1018, 01218-1450, 01218-1453, 01218-2020, 01218-2023, 01218-2570, 01218-2573, 01218-3000, 01218-3005, 01218-3007, 01218-3043, 01218-3080, 01218-3083, 01218-3510, 01218-3513, 01218-3700, 01218-3703, 01218-3710, 01218-3713, 01218-3720, 01218-3723, 01218-3760, 01218-3763, 01218-4000, 01218-4043, 01218-4080, 01218-4083, 01218-4550, 01218-4910, 01218-4913, 01218-5080, 01218-5083, 01218-5110, 01218-5113, 01218-5160, 01218-5163, 01218-5770, 01218-5773, 01218-5800, 01218-5803, 01218-5910, 01218-5913, 01218-6500, 01218-6503, 01218-7000, 01218-7003, 01218-7050, 01218-7053, 01218-7250, 01218-7253, 01218-7630, 01218-7633, 01218-8000, 01218-8003, 01218-8050, 01218-8053, 01218-8160, 01218-8163

MATERIAL SAFETY DATA SHEET
OSHA Hazard Communication
Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 7/02/01 at 09:42:10

Material Identity Jacquard Dye-na-Flow

SECTION VI HEALTH HAZARD DATA

Routes of Entry: Inhalation Vapors can be inhaled; not likely in toxic amts..
Skin Not likely in toxic amounts. Ingest. Very young children may drink paint. Keep paint out of reach.

Health Hazards None known for the usual and ordinary uses of this product.
NTP Carcinogen N/L IARC Carcinogen N/L OSHA Carcinogen N/L
Signs/Symptoms Symptoms of irritation are not likely to occur when using this
of Exposure and similar water based latex paint mixtures.
Medical Conditions N/K
to Avoid
First Aid Eye contact: Carefully flush for 15 minutes. If irritation persists, contact physician. Skin: Wash with soap and water. Inhalation: Remove to fresh air.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Contain spill. Spill area will be slippery. Recover as much as possible for reuse. Spread commercial absorbant over remainder and place into sealed container for disposal.
Waste Disp Dispose of all waste material in accordance with all applicable Federal, State and Local regulations. Most states prohibit disposal of liquids in landfills.
Precautions None are likely to be needed.
Other Precautions As with all chemicals good industrial hygiene and proper work habits should be observed.

SECTION VIII CONTROL MEASURES

Resp. Protect. Not usually required.
Local Exhaust May be used to prevent routine inhalation.
Spec. Local. Exh. N/A
Mech. Exhaust Mechanically exhaust vapors at point(s) of application.
Other Mech. Exhaust N/A
Protect. Gloves Not normally needed.
Eye Protect Splash goggles
Protect. Clothing N/A
Work Practices As with all chemicals, good industrial hygiene and proper work habits should be observed. Clean up work area after use.

Confirm all information prior to use

Abbreviations: Not Applicable N/A.. Not Flammable N/F
Not Known N/K

Ceiling Value C
Not Determined N/D
Not Listed N/L
TLV TLV

Permissible Exposure Limit PEL ACGIH Threshold Limit Value
The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any application or purpose. No other warranty is given.

Members: 0118-1999, 0118-1850, 0118-1851, 0118-1852, 0118-1853, 0118-1854, 0118-1855, 0118-1856, 0118-1857, 0118-1858, 0118-1859, 0118-1860, 0118-1861, 0118-1862, 0118-1863, 0118-1864, 0118-1865, 0118-1866, 0118-1867, 0118-1868, 0118-1869, 0118-1870, 0118-1871, 0118-1872, 0118-1873, 0118-1874, 0118-1875, 0118-1876, 0118-1877, 0118-1878, 0118-1879, 0118-1880, 0118-1881, 0118-1882, 0118-1883, 0118-1884, 0118-1885, 0118-1886, 0118-1887, 0118-1888, 0118-1889, 0118-1890, 0118-1891, 0118-1892, 0118-1893, 0118-1894, 0118-1895, 0118-1896, 0118-1897, 0118-1898, 0118-1899, 0118-1900, 0118-1901, 0118-1902, 0118-1903, 0118-1904, 0118-1905, 0118-1906, 0118-1907, 0118-1908, 0118-1909, 0118-1910, 0118-1911, 0118-1912, 0118-1913, 0118-1914, 0118-1915, 0118-1916, 0118-1917, 0118-1918, 0118-1919, 0118-1920, 0118-1921, 0118-1922, 0118-1923, 0118-1924, 0118-1925, 0118-1926, 0118-1927, 0118-1928, 0118-1929, 0118-1930, 0118-1931, 0118-1932, 0118-1933, 0118-1934, 0118-1935, 0118-1936, 0118-1937, 0118-1938, 0118-1939, 0118-1940, 0118-1941, 0118-1942, 0118-1943, 0118-1944, 0118-1945, 0118-1946, 0118-1947, 0118-1948, 0118-1949, 0118-1950, 0118-1951, 0118-1952, 0118-1953, 0118-1954, 0118-1955, 0118-1956, 0118-1957, 0118-1958, 0118-1959, 0118-1960, 0118-1961, 0118-1962, 0118-1963, 0118-1964, 0118-1965, 0118-1966, 0118-1967, 0118-1968, 0118-1969, 0118-1970, 0118-1971, 0118-1972, 0118-1973, 0118-1974, 0118-1975, 0118-1976, 0118-1977, 0118-1978, 0118-1979, 0118-1980, 0118-1981, 0118-1982, 0118-1983, 0118-1984, 0118-1985, 0118-1986, 0118-1987, 0118-1988, 0118-1989, 0118-1990, 0118-1991, 0118-1992, 0118-1993, 0118-1994, 0118-1995, 0118-1996, 0118-1997, 0118-1998, 0118-1999, 01218-7000, 01218-7003, 01218-7050, 01218-7053, 01218-7250, 01218-7253, 01218-7630, 01218-7633, 01218-8000, 01218-8003, 01218-8050, 01218-8053, 01218-8160, 01218-8163