

LinoSAFE Linoleum/Stone Stripper

HMIS NFPA			Personal protective equipment
Health	3	3	and South and
Fire Hazard	0	0	
Reactivity	0	0	

Version Number: 2 Preparation date: 2010-04-26

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LinoSAFE Linoleum/Stone Stripper

MSDS #: MS0300433 **Product Code:** 04188

Recommended use: Industrial/Institutional. Floor stripper.

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 8310 16th St.

Sturtevant, Wisconsin 53177-1964

Phone: 1-888-352-2249

MSDS Internet Address: www.diversey.com

Canadian Headquarters Diversey, Inc. - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1

Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'I)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER, CORROSIVE, CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principal routes of exposure: Eye contact. Skin contact. Inhalation.

Eve contact: Corrosive. Causes permanent eye damage, including blindness.

Corrosive. Causes permanent damage. Skin contact:

May cause irritation and corrosive effects to nose, throat and respiratory tract. Inhalation:

Ingestion: Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
2-butoxyethanol	111-76-2	5 - 10%	470	220 mg/kg	2.21 mg/L (4 h) 450 ppm (4 h)
Diethylene glycol butyl ether	112-34-5	10 - 20%	3384	2700 mg/kg	Not available
Ethylene glycol phenyl ether	122-99-6	5 - 10%	1260	5 mL/kg	Not available
Monoethanolamine	141-43-5	0.1 - 1.5%	1720	1 mL/kg 1025 mg/kg	Not available

4. FIRST AID MEASURES

Eye contact: Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact: Immediately flush with plenty of water for 15-20 minutes . Get medical attention immediately.

Inhalation: If breathing is affected, remove to fresh air. Get medical attention immediately.

If swallowed, rinse mouth. Give a cupful of water or milk . THEN IMMEDIATELY CONTACT A Ingestion: PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc.,

may be more susceptible to irritating effects

5. FIRE-FIGHTING MEASURES

The product is not flammable. Extinguish fire using agent suitable for surrounding fire. Suitable extinguishing media:

Specific hazards: Not applicable

Unusual hazards: Corrosive material (See sections 8 and 10).

Specific methods: No special methods required

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions Use appropriate containment to avoid environmental contamination. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Keep in suitable and closed and clean-up methods:

containers for disposal. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERICAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves

Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program Respiratory protection:

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Handle in accordance with good industrial hygiene and safety practice Hygiene measures:

Ingredient(s)	CAS#	ACGIH	OSHA	Mexico
2-butoxyethanol	111-76-2	20 ppm (TWA)	Skin	75 ppm (STEL) 360 mg/m ³
			50 ppm (TWA) 240 mg/m ³	(STEL)
			(TWA)	26 ppm (TWA) 120 mg/m ³
				(TWA)
Monoethanolamine	141-43-5	6 ppm (STEL)	3 ppm (TWA) 6 mg/m ³	6 ppm (STEL) 15 mg/m ³
		3 ppm (TWA)	(TWA)	(STEL)
				3 ppm (TWA) 8 mg/m ³
				(TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Bulk density: No information available Appearance: Liquid Evaporation Rate No information available

Specific gravity: 1.01 Color: Colorless Vapor density: No information available Odor: Solvent Boiling point/range: Not determined

Melting point/range: Not determined **Decomposition temperature:** Not determined

Solubility: Completely Soluble

Solubility in other solvents: No information available

Partition coefficient (n-octanol/water): No information available

Autoignition temperature: No information available

Density: 8.42 lbs/gal 1.01 Kg/L Flash point: > 200 °F > 93.4 °C Viscosity: No information available Elemental Phosphorus: 0 % by wt. VOC: 9 % *

pH: 9.8 Dilution pH: No information available.

Explosion limits: - upper: Not determined - lower: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: The product is stable

Polymerization: Hazardous polymerization does not occur

Hazardous decomposition products: None reasonably foreseeable.

Materials to avoid: Acids. Strong oxidising agents.

Conditions to avoid: Do not mix with any other product or chemical .

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Corrosive Oral LD50 estimated to be between 4000 - 5000 mg/kg

Component Information: See Section 3

Chronic toxicity: None known

Specific effects

 Carcinogenic effects:
 None known

 Mutagenic effects:
 None known

 Reproductive toxicity:
 None known

 Target organ effects:
 None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local applicable regulations.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, http://naextranet.diversey.com/dot/, for up to date shipping information.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
2-butoxyethanol	111-76-2	X	X	X	X
Diethylene glycol butyl ether	112-34-5	=	=	=	=
Ethylene glycol phenyl ether	122-99-6	=	=	=	=
Sodium xylene sulfonate	1300-72-7	=	=	=	-
Monoethanolamine	141-43-5	X	X	X	X
Water	7732-18-5	=	=	-	-

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol	111-76-2	5 - 10%			X
Ethylene glycol phenyl ether	122-99-6	5 - 10%			Х

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
2-butoxyethanol	X		
Ethylene glycol phenyl ether	X		

SARA 311/312 Hazard Categories Immediate: Χ Delayed: Fire: Reactivity: Sudden Release of Pressure:

WHMIS hazard class: E Corrosive material



16. OTHER INFORMATION

Not applicable NAPRAC Reason for revision: Prepared by: Additional advice: None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.