NORTH AMERICAN ADHESIVES & COATINGS COMPANY -- 2040350100 NA2040 ACRYLIC CERAMIC FLOOR & WALL TILE ADHESIVE -- 8040-00F052070

Product ID:2040350100 NA2040 ACRYLIC CERAMIC FLOOR & WALL TILE ADHESIVE MSDS Date:03/27/1990 FSC:8040 NIIN:00F052070 MSDS Number: CCZXM === Responsible Party === Company Name: NORTH AMERICAN ADHESIVES & COATINGS COMPANY Address:530 INDUSTRIAL DRIVE City:WEST CHICAGO State:IL ZIP:60185-1873 Country:US Info Phone Num: 708-231-7175 Emergency Phone Num: 708-231-7175 CAGE:GO638 === Contractor Identification === Company Name:NORTH AMERICAN ADHESIVES & COATINGS COMPANY Address:530 INDUSTRIAL DRIVE City:WEST CHICAGO State:IL ZIP:60185-1873 Country:US Phone: 708-231-7175 CAGE:GO638 Ingred Name: V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS *96-3* CAS:8032-32-4 RTECS #:016180000 Fraction by Wt: 3.0% Other REC Limits:STEL 400 PPM ACGIH TLV:300 PPM Ingred Name: METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS *96-3* CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: 1-2% Other REC Limits:200 PPM OSHA PEL:200 PPM ACGIH TLV:200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: IRRITATION & BURNING. SKIN: SLIGHT IRRITATION & DERMATITIS. INHALATION: MAY CAUSE IRRITATION TO NOSE & THROAT. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, BURNING, TEARING, REDNESS, PAIN, DISTRESS, NAUSEA.

file://jimepicpc/Users/Public/Epic%20Environmental%20Services%20(USE)/Product%20... 5/13/2016

Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN DISORDERS.

First Aid:EYES: FLUSH W/COPIOUS AMOUNTS OF CLEAN WATER. SKIN: WASH THOROUGHLY W/MILD SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: GIVE 3-4 GLASSES OF WATER. INDUCE VOMITING, IF CONSCIOUS UNDER DIRE CTIONS FROM A PHYSICIAN/POISON CONTROL CENTER. VOMITING CAN BE INDUCED BY GIVING 3 TBLS OF LIQUID DISHWASHING SOAP MIXED W/WATER. DON'T LEAVE VICTIM UNATTENDED. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:>200F

- Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER SPRAY & HALON 1211. Fire Fighting Procedures:WEAR SCBA.
- Unusual Fire/Explosion Hazard:PRODUCT WILL NOT BURN UNTIL WATER CONTENT HAS EVAPORATED. DECOMPOSITION BY PRODUCTS MAY BE TOXIC.

Spill Release Procedures:COVER W/ABSORBENT MATERIAL, TRANSFER TO CLOSED CONTAINERS.

Handling and Storage Precautions: KEEP FROM FREEZING. CLOSE CONTAINER AFTER USE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED Ventilation:MECHANICAL (GENERAL) &/LOCAL EXHAUST. Protective Gloves:IMPERVIOUS/RUBBER/BETTER Eye Protection:SAFETY GLASSES Supplemental Safety and Health

Boiling Pt:B.P. Text:209F Melt/Freeze Pt:M.P/F.P Text:32F Vapor Pres:AS WATER Vapor Density:AS WATER Spec Gravity:1.38 Evaporation Rate & Reference:SAME AS WATER Solubility in Water:DILUTETABLE Appearance and Odor:WHITE HEAVY PASTE W/ACRYLIC ODOR Percent Volatiles by Volume:33-35

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.