

[En Español](#) | [My Account](#) | [Shopping Cart](#) | [Contact Us](#) | [Store Locator](#)

[Shopping In-Store](#)

[Shopping Online](#)

SHOPPING CART

CURRENT VEHICLE No Vehicle Selected

Select a Vehicle

[NAPA STORE LOCATOR](#)

[GO](#)

[BROWSE ONLINE STORE](#)

[SEARCH NAPA CATALOG](#)

using PartsPRO SE

[SEARCH PARTS & ACCESSORIES](#)

by [Keyword](#) [GO](#) [Job Type Search](#)

QUICK LINKS

[NAPA Channel](#)

[NAPA Store Ownership](#)

[NAPA Rebates](#)

[NAPA Sponsorships](#)

[NAPA Careers](#)

[NAPA Training](#)

[Find a Repair Center](#)

[Find a Collision Center](#)

[Find a Truck Center](#)

[AAA](#)

[Integrated Business Solutions](#)

[Right to Repair](#)

WANT TO LEARN MORE ABOUT NAPA?

[Sign up for Email Updates](#)

Napa Premium Motor Oil 75-115

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 001

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: NON-DETERGENT MOTOR OIL SAE 30

SAP Material No: VV265

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

Company Telephone Numbers

The Valvoline Company Emergency: 1-800-274-5263

P.O. Box 14000

Lexington, KY 40512 Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s) CAS Number % (by volume)

HYDROTREATED HEAVY PARAFFINIC PETROLEUM DIST 64742-54-7 38.0- 48.0

HYDROTREATED LIGHT PARAFFINIC DISTILLATE 64742-55-8 38.0- 48.0

ALIPHATIC HYDROCARBON 64742-65-0 9.0- 19.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Unlikely to cause eye irritation or injury.

Skin

Prolonged or repeated contact may dry and crack the skin.

Additional symptoms of skin contact may include: acne, Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 002

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

Inhalation

Napa Premium Motor Oil 75-115

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects

No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Other Health Effects

No data

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 003

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

Primary Route(s) of Entry

Inhalation, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder

Napa Premium Motor Oil 75-115

clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 004

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

abnormalities. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

> 430.0 F (221.1 C)

Explosive Limit

Not applicable

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Fire and Explosion Hazards

Napa Premium Motor Oil 75-115

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 005

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

NFPA Rating

Health - 1, Flammability - 1, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot

Napa Premium Motor Oil 75-115

organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 006

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use. However, if misting or splashing conditions exist, then safety glasses or chemical splash goggles are advised.

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product. Wear normal work clothing covering arms and legs.

Respiratory Protections

Not required under normal conditions of use. However, if oil mists are generated above recommended PEL/TLV of 5 mg/m³, then a NIOSH/MSHA approved respirator is advised in absence of proper environmental control. (See your industrial hygienist.)

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines

Component

HYDROTREATED HEAVY PARAFFINIC PETROLEUM DISTILLATES (64742-54-7)

OSHA VPEL 5.000 mg/m³ - TWA

ACGIH TLV 5.000 mg/m³ - TWA

Napa Premium Motor Oil 75-115

HYDROTREATED LIGHT PARAFFINIC DISTILLATE (64742-55-8)

No exposure limits established

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 007

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

ALIPHATIC HYDROCARBON (64742-65-0)

OSHA VPEL 5.000 mg/m3 - TWA

ACGIH TLV 5.000 mg/m3 - TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

Not applicable

Vapor Pressure

Not applicable

Specific Vapor Density

< 1.000 @ AIR=1

Specific Gravity

.888 @ 60.00 F

Liquid Density

7.390 lbs/gal @ 60.00 F

.888 kg/l @ 15.00 C

Percent Volatiles (Including Water)

No data

Evaporation Rate

Appearance

No data

State

LIQUID

Physical Form

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 008

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

Color

AMBER

Odor

No data

pH
Not applicable

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 009

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

Napa Premium Motor Oil 75-115

MATERIAL SAFETY DATA SHEET

The Valvoline Company Page 010

Date Prepared: 06/05/06

Date Printed: 02/01/07

MSDS No: 505.0169702-008.015

NON-DETERGENT MOTOR OIL SAE 30

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate() Delayed() Fire() Reactive() Sudden

Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

[Return to Previous Page](#)

[Locations](#) | [About](#) | [Careers](#) | [Rebates](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#)

© Copyright 2009 National Automotive Parts Association. All rights reserved.