

Motor Oil 75-121

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- 75-121 PETROLEUM BASED LUBRICATING OIL -- 9150-00D020321

=====
Product Identification
=====

Product ID:75-121 PETROLEUM BASED LUBRICATING OIL

MSDS Date:10/17/1988

FSC:9150

NIIN:00D020321

MSDS Number: CCQZG

=== Responsible Party ===

Company Name:VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.

Address:200 E MAIN ST

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Info Phone Num:606-264-7000/7616;FAX 601-429-0537

Emergency Phone Num:800-ASHLAND/800-274-5263

CAGE:72527

=== Contractor Identification ===

Company Name:BALKAMP INC

Address:2601 S HOLT ROAD

Box:City:INDIANAPOLIS

State:IN

ZIP:46241

Country:US

Phone:317-244-7241

CAGE:70842

Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE

Address:ONE LINCOLN WAY

Box:City:ST. LOUIS

State:MO

ZIP:63120-1578

Country:US

Phone:414-255-5520

CAGE:050Q3

Company Name:VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

=====
Composition/Information on Ingredients
=====

Motor Oil 75-121

Ingred Name:MANUFACTURER LISTS NOTHING UNDER "INGREDIENTS" IMPLYING
THAT THERE ARE NO HAZARDOUS INGREDIENTS PER HAZ COM STD.
RTECS #:9999999ZZ
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TOXICOLOGICAL TESTING INDICATES THAT
SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR
1910.1200).
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-FLUSH WITH WATER FOR
15 MINUTES, LIFT LIDS. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH
SOAP & WATER. INHALED-REMOVE TO FRESH AIR. GIVE OXYGEN OR
ARTIFICIAL RE SPIRATION AS NEEDED. INGESTED-DO NOT INDUCE VOMITING!
KEEP PERSON WARM & QUIET.

=====
===== Fire Fighting Measures =====

Flash Point:>400F,>204C
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, REGULAR FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
FULL FIRE FIGHTER'S PROTECTIVE GEAR. WATER OR FOAM MAY CAUSE
FROTHING WHICH CAN BE VIOLENT-MAY ENDANGER FIRFIGHTER.
Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR
NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN
IGNITE EXPLOSIVELY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: ABSORB ON PAPER, VERMICULITE OR
OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD. LARGE SPILL: PREVENT
RUN-OFF INTO SEWERS, STREAMS OR OTHER BODIES OF WATER. CONTAIN
SPILL. TAKE UP MATERIAL (PUMP, ABSORB, ETC) AND PLACE IN WASTE
CONTAINERS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Motor Oil 75-121

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
DLA-HMIS: STORE IN A COOL, DRY PLACE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES. ALL HAZARD PRECAUTIONS GIVEN IN THE (MATERIAL SAFETY) DATA SHEET MUST BE OBSERVED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:NONE NORMALLY REQUIRED.
Protective Gloves:NONE NORMALLY REQUIRED.
Eye Protection:NONE NORMALLY REQUIRED.
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.
DLA-HMIS: EYE WASH STATION.
Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health
MFR MSDS NUMBER: 0171784-004.

=====
===== Physical/Chemical Properties =====

HCC:V6
Vapor Density:>1
Spec Gravity:0.881
Evaporation Rate & Reference:<1 (ETHER=1)
Appearance and Odor:CLEAR, BRIGHT LIQUID.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, VARIOUS HYDROCARBONS.
Conditions to Avoid Polymerization:CANNOT OCCUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:SMALL SPILL: ALLOW TO EVAPORATE. LARGE SPILL: DESTROY BY LIQUID INCINERATION. DLA-HMIS: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

Motor Oil 75-121

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.