

Pneumatic Tool Lub. BC601

STANLEY-BOSTITCH -- BC601 PNEUMATIC TOOL LUBRICANTS -- 9150-00F025509

=====
Product Identification
=====

Product ID:BC601 PNEUMATIC TOOL LUBRICANTS

MSDS Date:01/01/1991

FSC:9150

NIIN:00F025509

MSDS Number: BPSCV

=== Responsible Party ===

Company Name:STANLEY-BOSTITCH

Address:ROUTE 2

City:EAST GREENWICH

State:RI

ZIP:02818

Country:US

Info Phone Num:401-884-2500

Emergency Phone Num:401-884-2500

CAGE:0E7F8

=== Contractor Identification ===

Company Name:STANLEY-BOSTITCH

Address:ROUTE 2

Box:City:EAST GREENWICH

State:RI

ZIP:02818

Country:US

Phone:401-884-2500

CAGE:0E7F8

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY
PARAFFINIC, LUBRICATING OIL BASE STOCK

CAS:64741-88-4

RTECS #:PY8040500

OSHA PEL:5 MG/CUM

ACGIH TLV:5 MG/CUM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:
LUNG IRRITATION.

Explanation of Carcinogenicity:NONE

=====
First Aid Measures
=====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR

Pneumatic Tool Lub. BC601

15 MIN. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:141C/285F
Lower Limits:1%
Upper Limits:6%
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

=====
Accidental Release Measures
=====

Spill Release Procedures:PREVENT SPREAD OF SPILL, ABSORB W/SAND OR INERT MATERIALS, SWEEP OR SCOOP UP & REMOVE.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE METHODS GENERALLY ADVOCATED FOR PETROLEUM PRODUCTS. DON'T MIX W/OXIDIZING MATERIALS.
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W/SKIN, INHALATION OF FUMES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:AS REQUIRED
Ventilation:LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:GOGGLES
Other Protective Equipment:APRON
Work Hygienic Practices:DON'T WEAR CONTAMINATED CLOTHING.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Vapor Pres:<0.01
Vapor Density:>12
Spec Gravity:0.875
Evaporation Rate & Reference:(BU AC = 1): <0.01
Solubility in Water:NEGLIGIBLE
Appearance and Odor:PALE CLEAR LIQUID, PETROLEUM ODOR.
Percent Volatiles by Volume:NEGL

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS

Pneumatic Tool Lub. BC601

Hazardous Decomposition Products:CO

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.