

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** ULTRA BLACK GASKET MAKER 3.35OZ  
**Item No:** 82180  
**Product Type:** Elastomeric rubber

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
CALCIUM CARBONATE 471-34-1	40-50	10 mg/m <sup>3</sup> particulate TWA	Not Listed
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	30-40	Not Listed	Not Listed
POLYBUTYLENE RESIN 9003-29-6	10-20	Not Listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	1-10	Not Listed	Not Listed
STEARIC ACID 57-11-4	1-10	Not Listed	Not Listed
CARBON BLACK 1333-86-4	0.1-1.0	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA
2-BUTANONE OXIME 96-29-7	****	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation. \*\*\*\*When this product if exposed to moisture, butanone oxime may be formed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. May be harmful if swallowed. May irritate lips, gums, tongue, mouth, nose and throat.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation.

**Signs and Symptoms of Exposure:** Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
CARBON BLACK 1333-86-4	0.1-1.0		Group A4 - Not classifiable as a human carcinogen	Group 2B; Monograph 65, 1996

**Medical Conditions Recognized as Being Aggravated by Exposure:** None known

### 4. FIRST AID MEASURES

**Ingestion:** Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.  
**Skin Contact:** Wipe off paste with paper towel or cloth Wash off with soap and water If skin irritation persists, call a physician  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point (°F/C):** More than 200 degrees F. Method: Tag Closed Cup  
**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.  
**Special Fire-Fighting Procedures:** Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime., Silica fume, Oxides of carbon, Formaldehyde  
**Unusual Fire/Explosion Hazards:** None

**Lower Explosive Limit:** Not determined  
**Upper Explosive Limit:** Not determined

## **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

## **7. HANDLING AND STORAGE**

**Storage:** Store in a dry area below 90 degrees F. Keep container closed when not in use.  
**Handling:** Avoid contact with skin and eyes. Do not inhale vapors.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses.  
**Skin:** Rubber or plastic gloves.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.  
**Respiratory Protection:** Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Black paste  
**Odor:** MILD  
**Boiling Point:** Not applicable, polymeric material  
**pH:** Does not apply  
**Solubility in Water:** Polymerized  
**Specific Gravity:** 1.33  
**VOC Content(Wt.%):** 3.8% by weight  
**Vapor Pressure:** Less than 5 mm Hg @ 80 degrees F.  
**Vapor Density (Air=1):** 3.0  
**Evaporation Rate:** Not Determined

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** WILL NOT OCCUR  
**Incompatibilities:** Polymerized by contact with moisture. Strong oxidizers. Acids, Iron.  
**Conditions to Avoid:** Exposure to moisture  
**Hazardous Products of Combustion:** Oxides of nitrogen. Methyl ethyl ketone, possibly methyl ethyl ketoxime.. Silica fume. Oxides of carbon. Formaldehyde.

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

### **Domestic Ground Transport**

**DOT Shipping Name:** Unrestricted  
**Hazard Class:** None  
**UN/ID Number:** None

**Product name:** ULTRA BLACK GASKET MAKER  
3.35OZ

**Item No:** 82180

**Marine Pollutant:** None

**IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/NA Number:** None

**IMDG**

**Proper Shipping:** Unrestricted  
**Hazard Class:** None  
**UN Number:** None

**15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

**SARA 313 Information**

NONE

**CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present.

**TSCA Inventory Status:**

**Listed on Inventory:** **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA  
06106

**Revision Date:** 03/08/2004  
**Revision Number:** 3