MATERIAL SAFETY DATA SHEET

PRO-BOWL & PORCELAIN CLEANER Product Name: PRO-BOWL & PORCELAIN CLEANER Product Code: CELLO 1675 Product Class: Acid Cleaner

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CELLO PROFESSIONAL PRODUCTS, SHERWIN WILLIAMS CHEMICAL BUSINESS UNIT ADDRESS: 1354 Old Post Rd., Havre de Grace, MD. 21078 EMERGENCY PHONE: 800-522-3556 - CHEMTREC PHONE: 800-424-9300 - INFORMATION PHONE: 410-939-1234 DATE OF PREPARATION: 7/31/03 NAME OF PREPARER: Technical Department

	SECTION II - HAZARDOUS INGREDIENTS/ SARA III INFORMATION		
REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mmHg @ TEMP	PERCENT
#*HYDROGEN CHLORIDE	7647-01-0	114 77°F	9.00
OSHA: TWA 5ppm			
ACGIH: TWA 5ppm			

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. # Indicates hazardous chemical(s) subject to the reporting requirements of section 312 of Title III and of 40 CFR 370.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

SPECIFIC GRAVITY (H20=1): 1.05 VAPOR PRESSURE: NE SOLUBILITY IN WATER: COMPLETELY ODOR: SWEET VOLATILE: 99.34%

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NONE FLASH METHOD: SETA FLASH FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A HIGHER: N/A EXTINGUISHING MEDIA: IF INVOLVED IN A FIRE USE FOAM, CO2, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES: Spray water on cartons involved in fire to keep them from igniting. Wear self-contained breathing apparatus due to the possible toxic fumes from plastic containers and or the vaporization of potentially harmful chemicals. (See Section II).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Area will become slippery if material is released.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

BOILING POINT: 200 °F

pH: 1

VAPOR DENSITY: HEAVIER THAN AIR

APPEARANCE: PINK OPAQUE LIQUID

EVAPORATION RATE: SLOWER THAN WATER

CONDITIONS TO AVOID: AVOID PROLONGED CONTACT WITH SOFT METALS SUCH AS ALUMINUM, TIN AND ZINC.

INCOMPATIBILITY (MATERIALS TO AVOID): ALKALINE MATERIALS, OXIDIZING AGENTS, CONTACT WITH METALS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: HYDROGEN CHLORIDE GAS, HYDROGEN GAS, CHLORINE GAS, NITROGEN, CARBON DIOXIDE, CARBON MONOXIDE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: HIGH CONCENTRATIONS ARE IRRITATING TO EYES AND RESPIRATORY TRACT. MAY CAUSE HEADACHE, DIZZINESS, NAUSEA AND VOMITING.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CORROSIVE TO SKIN, COULD CAUSE BLINDNESS IF GOTTEN IN EYES. SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: ABSORPTION THROUGH SKIN MAY CAUSE HEADACHE, NAUSEA, DIZZINESS AND VOMITING. INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: HARMFUL IF SWALLOWED, MAY CAUSE BURNS TO THE MOUTH AND ESOPHAGUS. HEALTH HAZARDS (ACUTE AND CHRONIC): CONTACT WITH EYES CAN CAUSE CORNEAL DAMAGE. EXTENDED OVEREXPOSURE CAN CAUSE KIDNEY/LIVER DAMAGE, DIZZINESS, HEADACHES, NAUSEA, VOMITING.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO NOT LISTED

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: PRE-EXISTING PULMONARY, LIVER AND/OR KIDNEY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

EMERGENCY AND FIRST AID PROCEDURES:

IF IN EYES: Immediately flush with plenty of warm water for 15 minutes while keeping eyelids apart for maximum irrigation. If irritation persists contact physician.

IF ON SKIN: Wash off with large amounts of soap and water. If irritation persists contact a physician. Wash contaminated clothing before re-use.

IF INHALED: If victim complains of headache, dizziness or nausea, remove victim to fresh air. If breathing becomes difficult or condition persists, contact a physician.

IF INGESTED: Rinse mouth with water. Drink milk of magnesia or lime water. If these are not available drink large quantities of water. Do not induce vomiting. Seek immediate medical attention. Never give anything by mouth to an unconscious victim.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike area to contain material. Area may become slippery. Neutralize with lime or soda ash. Absorb product onto porous material such as sand, diatomaceous earth or commercial absorbent material. Shovel up into leak proof containers.

WASTE DISPOSAL METHOD: Consult local, state and or federal authorities for proper disposal.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near oxidizers, alkalies and base metals. Keep from excessive heat and keep from freezing. Do not store near consumables. Keep out of reach of children.

OTHER PRECAUTIONS: Read and follow all directions. Use in a manner consistent with product intent.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: NIOSH APPROVED VAPOR RESPIRATOR IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

VENTILATION: GOOD VENTILATION IS REQUIRED. IN THE ABSENCE OF GOOD VENTILATION MECHANICAL DEVICES ARE RECOMMENDED.

PROTECTIVE GLOVES: CHEMICAL RESISTANT GLOVES RECOMMENDED.

EYE PROTECTION: SAFETY SPLASH GOGGLES RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: SOLVENT RESISTANT CLOTHING AND BOOTS ARE RECOMMENDED. WORK/HYGIENIC PRACTICES: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

SECTION IX - REGULATORY INFORMATION

ALL INGREDIENTS OF THIS PRODUCT ARE LISTED ON THE US TOXIC SUBSTANCE CONTROL ACT (TSCA) INVENTORY.

HAZARD CLASS: WHEN SHIPPED IN 1 QUART CONTAINERS OR LESS: CONSUMER COMMODITY ORM-D

LARGER THAN QUARTS: CORROSIVE LIQUID, NOS (CONTAINS HYDROCHLORIC ACID) 8, UN1760, P.G. II

DOT LABEL: WHEN SHIPPED IN QUANTITIES OF 1 QUART OR LESS: ORM-D LARGER THAN QUARTS: CORROSIVE

The ingredients from Section II are subject to the following reporting requirements:

MA- The Massachusetts Hazardous Substance List

NJ- The New Jersey Right-to-Know Hazardous Substance List

PA- The Pennsylvania Substance List

SECTION X - DISCLAIMER

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended or implied as to the applicability of this information to the users intended purpose or for the consequences of its use or misuse.



HMIS HAZARD RATING:

3

0

0

D

HEALTH

FLAMMABILITY

REACTIVITY

PERSONAL PROTECTION

RATINGS:

4 - EXTREME

3 - SERIOUS

SUGHT

0 - MINIMUM

2 - SIGNIFICANT