

Material Safety Data Sheet



PUR-OSOL OVEN/GRILL CLEANER

Section 1. Chemical product and company identification

Trade name : PUR-OSOL OVEN/GRILL CLEANER
 Product use : Cleaning product
 Supplier : Puritan Services Inc.
 655 Lone Oak Drive
 Eagan MN 55121
 1-800-275-8914
 Code : 902139
 Date of issue : 28-April-2006

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	% by weight
sodium hydroxide	1310-73-2	7
2-(2-butoxyethoxy)ethanol	112-34-5	3
Surfactants	NJTSRN	5 - 20
	0409021390206	
petroleum gases, liquefied, sweetened	68476-86-8	1 - 5

Section 3. Hazards identification

Physical state : Liquid. (Aerosol.)
 Emergency overview : DANGER!

CAUSES EYE AND SKIN BURNS.
 CAUSES SEVERE RESPIRATORY TRACT IRRITATION.
 Can cause central nervous system depression.
 HARMFUL IF SWALLOWED.
 CONTENTS UNDER PRESSURE.

Do not ingest. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Avoid all possible sources of ignition (spark or flame). Keep away from heat and direct sunlight. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight.

Potential acute health effects

Eyes : Corrosive to eyes.
 Skin : Corrosive to the skin.
 Inhalation : Severely irritating to the respiratory system. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.
 Ingestion : Harmful if swallowed. Causes burns to mouth, throat and stomach.
 See toxicological information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.
 Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
 Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
 Ingestion : Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

PUR-OSOL OVEN/GRILL CLEANER

Page: 2/4

Section 5. Fire fighting measures

Flash point	: > 100°C
Flammable limits	: Lower: 1.9 % Upper: 9.8 %
Fire-fighting media and instructions	: Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to fire with water. Bursting aerosol containers may be propelled from a fire at high speed. Dike liquid for later disposal. No specific hazard.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions	: Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for cleaning up	: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling	: Do not ingest. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Storage	: Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 50°C

Section 8. Exposure controls, personal protection

Engineering controls	: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Provide eyewash and safety shower in area if contact or splash hazard exists.
----------------------	--

Personal protection

Eyes	: Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.
Hands	: Use chemical-resistant, impervious gloves.
Skin	: Wear suitable protective clothing.
Respiratory	: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Name

sodium hydroxide

Exposure limits**OSHA PEL (United States, 8/1997).**TWA: 2 mg/m³ 8 hour(s). Form: All forms**ACGIH TLV (United States, 1/2004).**CEIL: 2 mg/m³CEIL: 2 mg/m³ Form: All forms**ACGIH TLV (United States, 1/2005).**

TWA: 1000 ppm 8 hour(s). Form: All forms

ACGIH TLV (United States, 1/2005).

TWA: 1000 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997).TWA: 1800 mg/m³ 8 hour(s). Form: All forms

TWA: 1000 ppm 8 hour(s). Form: All forms

butane (Containing >= 0.1 %

butadiene (203-450-8))

propane

PUR-OSOL OVEN/GRILL CLEANER

Page: 3/4

Section 9. Physical and chemical properties

Physical state : Liquid. (Aerosol.)
 Color : Colorless.
 Odor : citrus
 pH : 13.5 (100%)
 Specific gravity : 0.9768 (Water = 1)

Section 10. Stability and reactivity

Stability : The product is stable.
 Reactivity : Reactive with organic materials, metals, acids, alkalis.

Section 11. Toxicological information**Potential acute health effects**

Eyes : Corrosive to eyes.
 Skin : Corrosive to the skin.
 Inhalation : Severely irritating to the respiratory system. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.
 Ingestion : Harmful if swallowed. Causes burns to mouth, throat and stomach.

Potential chronic health effects

Chronic effects on humans : Contains material which causes damage to the following organs: lungs, upper respiratory tract, skin, eye, lens or cornea.

Section 12. Ecological information

Products of degradation : These products are carbon oxides (CO, CO₂) and water. Some metallic oxides.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification		Consumer commodity	ORM-D	-	-

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification : Corrosive material
 Target organ effects
 U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: No products were found.
 SARA 302/304 emergency planning and notification: No products were found.
 TSCA 8(b) inventory : All materials are listed or exempt.
SARA 313 Product name Concentration

Form R - Reporting requirements: 2-(2-butoxyethoxy)ethanol
 California Prop. 65 : No products were found.

1 - 5

PUR-OSOL OVEN/GRILL CLEANER

Page: 4/4

Section 16. Other information

Hazardous Material Information System (U.S.A.)	:	<table border="1"> <tr> <td>Flammability</td> <td>3</td> </tr> <tr> <td>Corrosivity</td> <td>2</td> </tr> <tr> <td>Reactivity</td> <td>0</td> </tr> <tr> <td>Personal protection</td> <td>B</td> </tr> </table>	Flammability	3	Corrosivity	2	Reactivity	0	Personal protection	B
Flammability	3									
Corrosivity	2									
Reactivity	0									
Personal protection	B									

Date of issue : 28-April-2006.
 Responsible name : Regulatory Affairs
 Date of previous issue : 04-August-2005.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.