

TRUE FLOW CLEAR GLOSS SPRAY

RZ000472.TXT

Rcvd Jan 2006

466340/317-253

Issued to : School Specialty
Sax Arts and Craft
P.o. Box 1017

Appleton WI 54912-1017

Attention: : Material Safety Data Sheet Coordinator

The attached Material Safety Data Sheet relates potential hazards and recommended practices for safe handling of the product that you purchased from Raabe Company.

We urge you and your employees to review the entire MSDS prior to handling, use or disposal of the product.

You are required to keep this MSDS on file for reference by company employees or government regulatory officials.

If you resell or distribute this product, you must furnish a copy of the MSDS to your customer.

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE. : 01050 000472 604
PRODUCT NAME : GLOSS CLEAR
PRODUCT CLASS : Aerosol Product

MSDS PREPARATION DATE : 01/12/2006

MANUFACTURER IDENTIFICATION:

RAABE COMPANY
PO BOX 1090

MENOMONEE FALLS WI 53052-1090

CUSTOMER IDENTIFICATION:

School Specialty
Sax Arts and Craft
P.o. Box 1017

Appleton WI 54912-1017

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ETHYLBENZENE

CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: 3.7970 VAPOR PRESSURE: 19.000 MMHG @ 68F LEL 1.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 125 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL 125 ppm

OTHER

RZ000472.TXT
IARC (2B), CALIFORNIA PROP 65 (Cancer 6/11/2004)

2 N-BUTANE
CAS# 106-97-8
N-BUTANE
PCT BY WT: 12.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80
EXPOSURE LIMIT:
ACGIH TLV-TWA 800 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 800 ppm
COMPANY N.E.

3 PROPANE
CAS# 74-98-6
PROPANE
PCT BY WT: 16.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20
EXPOSURE LIMIT:
ACGIH TLV-TWA 1000 ppm
ACGIH TLV-STEL NO INFORMATION

4 XYLENE
CAS# 1330-20-7
XYLENE
PCT BY WT: 16.0000 VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00
EXPOSURE LIMIT:
ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 150 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL 150 ppm
COMPANY N.E.
LD50(ORAL) 4300 mg/kg
LD50(DERMAL) 1700 mg/kg
LC50 18892 mg/m3

5 ACETONE
CAS# 67-64-1
ACETONE
PCT BY WT: 19.0000 VAPOR PRESSURE: 231.000 MMHG @ 68F LEL 2.60
EXPOSURE LIMIT:
ACGIH TLV-TWA 750 ppm
ACGIH TLV-STEL 1000 ppm
OSHA PEL-TWA 750 ppm
OSHA PEL-STEL 1000 ppm
COMPANY N.E.

6 2-BUTOXYETHANOL
CAS# 111-76-2
2-BUTOXYETHANOL
PCT BY WT: 3.0000 VAPOR PRESSURE: .880 MMHG @ 68F LEL 1.10
EXPOSURE LIMIT:
ACGIH TLV-TWA 25 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 25 ppm
COMPANY N.E.

7 TOLUENE
CAS# 108-88-3
TOLUENE
PCT BY WT: 20.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40
EXPOSURE LIMIT:
ACGIH TLV-TWA 50 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 50 ppm

COMPANY N.E.
OTHER LIMITS:
Prop 65-Developmental-01/01/91

 This product contains one or more reported carcinogens or suspected
 carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits
 recommended column.

 This substance is classified as a hazardous air pollutant.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- Harmful if swallowed.
- Harmful if inhaled.
- Causes eye irritation.
- Causes skin irritation.
- Vapors irritating to eyes and respiratory tract.
- Extremely flammable liquid and vapor.
- Vapors may cause flash fire or explosion.
- Extremely flammable aerosol.
- Contents under pressure.

EYE:

May cause severe eye irritation.

SKIN:

- May cause skin irritation.
- Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
- Product contains a component which can be absorbed through the skin.
- Excessive exposure may cause hemolysis (red blood cell damage) which can impair the blood's ability to transport oxygen.
- Material may aggravate an existing dermatitis.

INHALATION:

- Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
- Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
- Liquid or vapor may be irritating to skin, eyes, throat or lungs.
- Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:

- Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.
- Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Blood damage
- Lung damage
- Liver damage
- Spleen damage
- Anemia
- Brain damage
- Reproductive system damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

Liver damage

Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

2-Butoxyethanol causes harm to the fetus in laboratory animal studies.

Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint	: Less Than -25 °F
Explosion Level	: Low (LEL)- 1.0
	High (UEL)- 12.8

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat.

Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst.

Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

Use water spray to disperse vapors. Minimize breathing gases, vapor, fumes or decomposition products. Use self-contained breathing apparatus with full face piece operated in positive pressure mode as needed.

SECTION 7 - HANDLING AND STORAGE-----
HANDLING:

Wash hands thoroughly after handling.

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION-----
ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	: 5585.20	mm Hg @ 20 C
Vapor Density	: 3.70	
Boiling Range	: Lower - 1.0	øF
	: Higher - 340.0	øF
Specific Gravity	: .739	
Formula weight per volume	: 6.1549	LB/GL
VOC (Calculated, LB/GAL)	: 5.252	
VOC (Calculated, GM/L)	: 629.34	
Percent Volatile by weight	: 90.2035	
Percent Volatile by volume	: 93.3283	
Evaporation Rate	: 7.700	(n-Butyl Acetate = 1)
Viscosity	: N/A	

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.
Product may explode if heated. Keep cool, avoid exposure to heat.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 3.7970

XYLENE

CAS# 1330-20-7 PCT BY WT: 16.1880

 2-BUTOXYETHANOL
 CAS# 111-76-2 PCT BY WT: 2.9970

TOLUENE
 CAS# 108-88-3 PCT BY WT: 20.1810

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

CHEMICAL NAME	CAS NUMBER
Acrylic Polymer	Not Listed

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

 The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2* FLAMMABILITY: 4 REACTIVITY: 0 PERSONAL PROTECTION: G