

UNITED COATINGS INC -- 5407, WHITE, WALMART COLOR PLACE LATEX (SUPP DATA) -- 8010-00N079558

=====

MSDS Safety Information

=====

FSC: 8010
 MSDS Date: 09/30/1993
 MSDS Num: CFLWL
 LIIN: 00N079558
 Tech Review: 10/16/1997
 Product ID: 5407, WHITE, WALMART COLOR PLACE LATEX (SUPP DATA)
 Responsible Party
 Cage: UNITD
 Name: UNITED COATINGS INC
 Address: 2850 FESTIVAL DR
 City: KANKAKEE IL 60901 US
 Info Phone Number: 800-782-7889
 Emergency Phone Number: 800-621-1000
 Review Ind: N

=====

Contractor Summary

=====

Cage: UNITD
 Name: UNITED COATINGS INC
 Address: 2850 FESTIVAL DR
 City: KANKAKEE IL 60901 US
 Phone: 800-782-7889/800-621-1000

=====

Ingredients

=====

Cas: 25265-77-4
 RTECS #: UF6000000
 Name: PROPIONIC ACID, 2-METHYL-, MONOESTER
 W/2,2,4-TRIMETHYL-1,3-PENTANEDIOL
 % by Wt: <5
 OSHA PEL: N/K (FP N)
 ACGIH TLV: N/K (FP N)
 Ozone Depleting Chemical: N

Cas: 107-21-1
 RTECS #: KW2975000
 Name: ETHYLENE GLYCOL (SARA 313) (CERCLA)
 % by Wt: <5
 OSHA PEL: N/K (FP N)
 ACGIH TLV: 50 PPM, VAPOR, C
 EPA Rpt Qty: 1 LB
 DOT Rpt Qty: 1 LB
 Ozone Depleting Chemical: N

Cas: 21645-51-2
 RTECS #: BD0940000
 Name: ALUMINUM HYDROXIDE; (AL(OH)*3)
 % by Wt: <5
 OSHA PEL: N/K (FP N)
 ACGIH TLV: N/K (FP N)
 Ozone Depleting Chemical: N

Cas: 13463-67-7
 RTECS #: XR2275000
 Name: TITANIUM OXIDE; (TITANIUM DIOXIDE)
 % by Wt: 20-25
 OSHA PEL: 15 MG/M3 TDUST
 ACGIH TLV: 10 MG/M3 TDUST
 Ozone Depleting Chemical: N

Cas: 1332-58-7

RTECS #: GF1670500
 Name: CLAY (KAOLIN); (HYDROUS ALUMINUM SILICATE)
 % by Wt: <5
 OSHA PEL: 15 MG/M3 TDUST
 ACGIH TLV: 2 MG/M3 TDUST
 Ozone Depleting Chemical: N

 Name: VOLATILE ORGANIC COMPOUNDS: UNKNOWN.

Health Hazards Data

=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
 Route Of Entry Inds - Inhalation: NO
 Skin: YES
 Ingestion: NO
 Carcinogenicity Inds - NTP: NO
 IARC: NO
 OSHA: NO
 Effects of Exposure: IRRITATES SKIN. ABSORBED THROUGH SKIN.
 Explanation Of Carcinogenicity: NOT RELEVANT
 First Aid: GET MEDICAL ATTENTION IMMEDIATELY IF NEEDED. INHAL:REMOVE
 PATIENT. KEEP AN OPEN AIRWAY. MONITOR BREATHING. INGEST:DO NOT INDUCE
 VOMITING. DILUTE W/WATER. CALL POISON CONTROL. EYES:DECONTAMINATE PATIENT.
 T. IRRIGATE FOR AT LEAST 15 MINUTES. SKIN:DECONTAMINATE PATIENT.
 IRRIGATE.

Handling and Disposal

=====

Spill Release Procedures: MOP UP OR SOAK UP SUBSTANCE. THIS PRODUCT DOES
 NOT CONTAIN OR MANUFACTURED W/ANY OZONE DEPLETING CHEMICALS.
 Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
 Waste Disposal Methods: DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL
 REGULATIONS (FP N). DISPOSE OF IN AN ENVIRONMENTALLY SAFE METHOD.
 Handling And Storage Precautions: KEEP AWAY FROM EXCESSIVE HEAT TO PREVENT
 PRESSURE BUILD UP IN A CLOSED CONTAINER.
 Other Precautions: KEEP AWAY FROM HEAT. AVOID CONTACT W/SKIN OR EYES.
 VENTILATION REQUIRED.

Fire and Explosion Hazard Information

=====

Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE (FP N).
 NON-FLAMMABLE.
 Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE
 EQUIPMENT (FP N).
 Unusual Fire/Explosion Hazard: NONE.

Control Measures

=====

Respiratory Protection: NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE
 OF CONCERN (FP N). NONE NORMALLY NECESSARY.
 Ventilation: LOCAL EXHAUST:GOOD, ROOM, CROSS VENTILATION IS ADEQUATE.
 Protective Gloves: PLASTIC GLOVES.
 Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).
 Other Protective Equipment: ANSI APPROVED EYE WASH FOUNTAIN & DELUGE
 SHOWER (FP N). WEAR OLD CLTHG THAT CAN BE DISCARDED IF CLTHG SHOULD
 (SUPDAT)
 Work Hygienic Practices: WASH HANDS BEFORE EATING, DRINKING, SMOKING OR
 USING TOILET FACILITIES. DO NOT EAT OR DRINK WHILE USING THIS PRODUCT.
 Supplemental Safety and Health: MFR'S TRADE NAME/PART NO:INTERIOR
 SEMI-GLOSS ENAMEL. OTHER PROT EQUIP:BECOME PAINT STAINED.

Physical/Chemical Properties

=====

B.P. Text: 212F,100C
 Vapor Density: HVR/AIR
 Spec Gravity: 1.279

Evaporation Rate & Reference: SLOWER THAN BUTYL ACETATE
 Solubility in Water: DILUTABLE
 Appearance and Odor: LIQUID; SLIGHT ODOR.

=====

Reactivity Data

=====

Stability Indicator: YES
 Stability Condition To Avoid: WHILE PRODUCT IS IN A SEALED CONTAINER IT
 MAY GENERATE PRESSURE WHEN HEATED.
 Hazardous Polymerization Indicator: NO
 Conditions To Avoid Polymerization: NOT RELEVANT

=====

Toxicological Information

=====

Ecological Information

=====

MSDS Transport Information

=====

Regulatory Information

=====

Other Information

=====

HAZCOM Label

=====

Product ID: 5407, WHITE, WALMART COLOR PLACE LATEX (SUPP DATA)
 Cage: UNITD
 Company Name: UNITED COATINGS INC
 Street: 2850 FESTIVAL DR
 City: KANKAKEE IL
 Zipcode: 60901 US
 Health Emergency Phone: 800-621-1000
 Date Of Label Review: 10/16/1997
 Label Date: 10/16/1997
 Chronic Hazard IND: N
 Eye Protection IND: YES
 Skin Protection IND: YES
 Signal Word: CAUTION
 Respiratory Protection IND: YES
 Health Hazard: Slight
 Contact Hazard: Slight
 Fire Hazard: None
 Reactivity Hazard: None
 Hazard And Precautions: ACUTE:IRRITATES SKIN. ABSORBED THROUGH SKIN.
 CHRONIC:NONE LISTED BY MANUFACTURER.

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.